



## Calder Washing Trough, 240cm Central Outlet Domed 2in Waste Tapholes for 4 mixers

### Illustrated

- S2826** Calder stainless steel washing trough 240cm long, 4 taphole positions, central outlet with 2" domed waste
- B8861** Avon 21 washbasin mixer 1 hole, self closing push button, variable temperature with copper tube inlets
- A5900** TMV Thermostatic mixing valve 15mm

### Configuration options

- A4169** Contour 21 washbasin mixer thermostatic 1 hole, single sequential long lever, copper tails
- B8260** Piccolo 21 washbasin 1 taphole mixer, fitted 5 litres per minute aerated flow regulator, optional flow straightener, EasyFix, temperature limit stop, flexible tails no pop up waste

### Material

Stainless Steel

### Weights

S2826	22.40KG
B8861	2.45KG
A5900	0.60KG

### Colours


Stainless Steel finish (MY)

### Standards

Stainless steel sheet to BS EN 10088:Part 2:2005

### Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900AA



### Frequently used applications

- Education
- Factory
- Public Building
- Sports and Leisure
- Vandal Risk

### Accreditations

- WRAS
- Water Label

*Armitage  
Shanks*

Email: [info@idealspec.co.uk](mailto:info@idealspec.co.uk)  
 Tel: 0870 122 8822  
 Fax: 0870 122 8282  
 Web: [www.idealspec.co.uk](http://www.idealspec.co.uk)

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by  
**Ideal**Spec

Date created:06/09/2016