

Contour 21 Thermostatic basin mixer with Bioguard

ILLUSTRATED

A6430 Contour 21 Thermostatic basin mixer with Bioguard

ILLUSTRATED PRODUCT DETAILS

Weights

A6430 2.70 KG

Finishes

A6430  Chrome (AA)

Materials

A6430 Chrome Plated
Brass

Designer



Robin Levien, RDI

Standards

Conforms to HTM64 (2006), HTM04 and Doc M.

Special Notes

Suitable for use with handrinse basins in public areas and Doc M. Satisfies DDA requirements. Meets the requirements laid out in HTM 64, HTM 04. Single easy use lever operates on/off and temperature control. Eliminates the need for premixed water. Suitable for high and low pressure systems. To ensure system hygiene and user safety the water flow always commences from cold. Traditional backnut fixing for added security. Fits into a standard pillar tap hole. Flow rate stays constant even when temperature setting is changed (providing supply pressure is 1.0 bar or higher). Thermostatically set to 41°C with single lever to control flow of water. Durable and easy to clean finish. Supplied complete with strainer/check valves and flow limiters. Serviceable from above the basin (once supplies are isolated). Cartridge based system for easy servicing/repair. Unregulated flow rate 5 litres per minute at 0.3 bar.



ACCREDITATIONS



Contour 21 Thermostatic basin mixer with Bioguard

FEATURES

