



Markwik 21 Panel Mixer, Demountable, Time Flow Sensor, Detachable Spout and Bioguard

Illustrated

A6245 (TB H6) Markwik 21 integral thermostat, demountable panel mixer, time flow sensor, detachable spout and Armitage Bioguard outlet fitted

Configuration options

Material

Chrome Plated Metal

Weights

A6245 5.80KG

Colours

Chromium plated (AA)

Flow rates

7.5 Litres per minute @ 3 bar pressure

Standards

Conforms to HBN 00.10, HBN 00.09 and HTM 04-01 Addendum 2013.

Special Notes

This product is fitted with an Armitage Bioguard outlet which reduces the opportunity for bio film attachment and is lined with anti-microbial copper.


Tap is activated by hand movement over the sensor and water will run for a predetermined length of time, factory pre-set at 1 minute but adjustable.

Hygienic automatic flush can be set to occur every 6, 12, 24, 48 or 72 hours.

Unique built-in thermal disinfection cleansing feature using kit S8239NU a bridging hose which is re-usable. A purging tool A4556AA is also available to facilitate initial installation or aid in system disinfection.

Flow rate regulated to maximum of 10 Litres per minute.

* Line drawing shows recommended height over scrub up troughs.



Frequently used applications

General Healthcare

Hospitals

Features

HTM

Accreditations

WRAS

*Armitage
Shanks*

Email: info@idealspec.co.uk
Tel: 0870 122 8822
Fax: 0870 122 8282
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
IdealSpec

Date created: 16/02/2017