

Sandringham 21 Washbasin Pillar Taps Lever Handles

Illustrated

B9881 Sandringham 21 washbasin pillar taps, lever handles

Configuration options

Material

Chrome Plated Brass

Weights

B9881 1.10KG

Colours

Chromium plated (AA)

Flow rates

8 Litres per minute @ 3 bar
pressure

Special Notes


Suitable for balanced/unbalanced supplies. Inlets screwed 1/2in BSP male, coned for copper. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see S7435AA. Water saving can be achieved by use of a flow regulators such as L6935NU to deliver maximum of 4 Litres per minute. Unregulated flow rate 8.2 litres per minute at 0.1 bar.

Frequently used applications

Education	Factory
General Healthcare	Hotels
Office	Public Building
Pubs and Clubs	Residential
Retail	Social Housing
Sports and Leisure	Student Accommodation

Accreditations

WRAS



*Armitage
Shanks*

Email: info@idealspec.co.uk
Tel: 0870 122 8822
Fax: 0870 122 8282
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
Ideal Spec

Date created: 28/09/2015