

## Sensorflow 21 Tubular 15cm Panel Mounted Spout & Separate Sensor, Link

### Illustrated

**A4181** Sensorflow 21 tubular panel mounted 150mm projection spout anti splash or aerated outlet remote panel sensor, copper tube inlets, link

### Configuration options

### Material

Chrome Plated Brass

### Weights

A4181 2.45KG

### Colours

Chromium plated (AA)  
Brushed Steel (GN)

### Flow rates

4.7 Litres per minute @ 3 bar pressure

### Special Notes

Designed to be supplied with pre-mixed water consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900. The proximity sensor should be positioned to work in the normal handwashing position. All spouts supplied complete with individual solenoid valve, copper tube inlet and combined servicing valve and filter. Automatically shuts off if sensor is obstructed for a maximum of 55 seconds. Must link to a mains version, alternatively a stand alone battery powered unit is available.


Flow rates, regulated to 5 Litres per minute or optional flow straightener outlet 2.8 Litres per minute @ 0.1 bar .

### Frequently used applications

Education	Factory
General Healthcare	Hotels
Office	Public Building
Pubs and Clubs	Retail
Sports and Leisure	Vandal Risk

### Features

Water Saving



Armitage  
Shanks

Tel: 0870 122 8822  
Fax: 0870 122 8282  
Email: [info@idealspec.co.uk](mailto:info@idealspec.co.uk)  
Web: [www.idealspec.co.uk](http://www.idealspec.co.uk)

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by  
**Ideal Spec**

Date created: 17/07/2014