

Sensorflow 21 Tubular 15cm Panel Mounted Spout & Separate Sensor- Battery

Illustrated

A4126 Sensorflow 21 tubular panel mounted 150mm projection spout anti splash or aerated outlet remote panel sensor, copper tube inlets, battery

Configuration options

Material

Chrome Plated Brass

Weights

A4126 2.10KG

Colours

Chromium plated (AA)
Brushed Steel (GN)

Flow rates

4.7 Litres per minute @ 3 bar pressure

Special Notes

Designed to be supplied with pre-mixed water consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900. The proximity sensor should be positioned to work in the normal handwashing position. All spouts supplied complete with individual solenoid valve, copper tube inlet and combined servicing valve and filter. Spouts with integral sensors detect hands within the sensing range and the solenoid valve is opened. Automatically shuts off if sensor is obstructed for a maximum of 55 seconds. A stand alone battery powered unit

Flow rates, regulated to 5 Litres per minute or optional flow straightener outlet 2.8 Litres per minute @ 0.1 bar .

Frequently used applications

Education	Factory
General Healthcare	Hotels
Office	Public Building
Pubs and Clubs	Retail
Sports and Leisure	Vandal Risk

Features

Water Saving

Accreditations

Water Label

