# Silhouette 300cm Washtrough With Upstand

## Illustrated

**S0636** Silhouette 300cm wash trough with upstand, 5 taphole

**A4849** Sensorflow 21 compact tubular panel mounted 230mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, mains

## Configuration options

**A4850** Sensorflow 21 compact tubular panel mounted 230mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, link

## Material

Solid Surface

## Weights

S0636 65.00KG
A4849 2.30KG

## Colours

White (01)

## Standards

EN 695
BS EN 14296

## Special Notes

1 Mains spout (A4849), 4 link spout (A4850) and 6 brackets (S0663) to be configured. Clean using a damp cloth or sponge. Wipe dry with a soft cloth to prevent spotting.

## Frequently used applications

Education
Office
Pubs and Clubs
Factory
Public Building
Sports and Leisure

Armitage Shanks

Email: info@idealspec.co.uk
Tel: 0870 122 8822
Fax: 0870 122 8282
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by IdealSpec

Date created:26/04/2016