Silhouette 120cm Washtrough With Upstand

Illustrated

S0633	Silhouette 120cm wash trough with upstand, 2 taphole
S0663	Silhouette 480mm washtrough bracket
A4849	Sensorflow 21 compact tubular panel mounted 230mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, mains

Configuration options

A4850	Sensorflow 21 compact tubular panel mounted 230mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, link

Material

Solid Surface

Weights

S0633	26.00KG
A4849	2.30KG

Colours

White (01)

Standards

EN 695
BS EN 14296

Special Notes

1 Mains spout (A4849), 1 link spout (A4850) and 4 brackets (S0663) to be configured. Clean using a damp cloth or sponge. Wipe dry with a soft cloth to prevent spotting.

Frequently used applications

Education	Factory
Office	Public Building
Pubs and Clubs	Sports and Leisure

Armitage Shanks

Email: info@idealspec.co.uk
Tel: 0870 122 8822
Fax: 0870 122 8282
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by IdealSpec

Date created:26/04/2016