








## ILLUSTRATED

<b>T9937</b>	Softmood 170 x 75cm double ended Idealform Plus+ bath, no tapholes
<b>A4609</b>	Attitude single lever one hole bath filler
<b>E4797</b>	Unilux Plus+ 170cm front panel for Idealform Plus+
<b>E4832</b>	Unilux Plus+ 75cm front bath panel for Idealform Plus+
<b>E5795</b>	Waste 1½" bath pop-up waste and overflow components only
<b>E5800</b>	Bath pop-up waste operating handle and cover only
<b>A5901</b>	TMV Thermostatic mixing valve 22mm

## ILLUSTRATED PRODUCT DETAILS

## Finishes

<b>T9937</b>	35.80 KG
<b>A4609</b>	2.65 KG
<b>E4797</b>	3.65 KG
<b>E4832</b>	2.58 KG
<b>E5795</b>	1.34 KG
<b>E5800</b>	0.82 KG
<b>A5901</b>	1.70 KG

<b>T9937</b>		White (01)
<b>A4609</b>		Chrome (AA)
<b>E4797</b>		White (01)
<b>E4832</b>		White (01)
<b>E5795</b>		Neutral / No Finish (67)
<b>E5800</b>		Chrome (AA)
<b>A5901</b>		Chrome (AA)

## Materials

<b>T9937</b>	Idealform Plus+
<b>A4609</b>	Chrome Plated Brass
<b>E4797</b>	Acrylic
<b>E4832</b>	Acrylic
<b>E5795</b>	Chrome Plated Metal
<b>E5800</b>	Chrome Plated Metal
<b>A5901</b>	Chrome Plated Metal

## Capacity

**T9937** 185 litres (to overflow)

## Flow rates

**A4609** 13.6 Litres per minute @  
3 bar pressure

Designer



## Artefakt Industriekultur

## Standards

Constructed to EN 198:2008. EN 14516

## Special Notes

All fittings can be replaced directly behind the overflow on T9937 Softmood 170 x 75cm Idealform double ended model. T9935 Softmood 170 x 70cm Idealform double ended bath, 2 taphole fittings can be positioned directly behind the overflow, all others require checking for compatibility before specifying.



## ACCREDITATIONS

**T9937(01)**



**A4609(AA)**

