

## Tempo Arc Idealform Double Ended Bath 170x75cm No Handgrips No Tapholes

### ILLUSTRATED

<b>E2566</b>	Tempo Arc 170 x 75cm Idealform double ended bath no handgrips no tapholes
<b>B0730</b>	Tempo 2 hole bath filler
<b>E4130</b>	Uniline 170cm front panel
<b>E4190</b>	Uniline 75cm end panel
<b>E1486</b>	1 1/2" Bath pop-up waste and overflow
<b>A5901</b>	TMV Thermostatic mixing valve 22mm

### ILLUSTRATED PRODUCT DETAILS







#### Weights

<b>E2566</b>	23.00 KG
<b>B0730</b>	2.64 KG
<b>E4130</b>	3.60 KG
<b>E4190</b>	3.30 KG
<b>A5901</b>	1.70 KG

#### Materials

<b>E2566</b>	Idealform
<b>B0730</b>	Chrome Plated
<b>E4130</b>	Acrylic
<b>E4190</b>	Acrylic
<b>E1486</b>	Mixed Material
<b>A5901</b>	Chrome Plated Metal

#### Finishes

<b>E2566</b>	 White (01)
<b>B0730</b>	 Chrome (AA)
<b>E4130</b>	 White (01)
<b>E4190</b>	 White (01)
<b>E1486</b>	 Chrome (AA)
<b>A5901</b>	 Chrome (AA)

#### Capacity

<b>E2566</b>	180 litres (to overflow)
--------------	--------------------------

#### Flow rates

<b>B0730</b>	50 Litres per minute @ 3 bar pressure
--------------	---------------------------------------

#### Designer


Robin Levien, RDI

#### Standards

Constructed to EN 198:2008. EN 14516

#### Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5901AA or Part G for guidance.



### ACCREDITATIONS

#### B0730(AA)

<b>water label</b> 		<b>50.00</b> Litres Per Minute
--	---	--------------------------------

#### E2566(01)

<b>water label</b> 		<b>180.0</b> Litres
--	---	---------------------