

## Markwik 21 Bib Mixer Thermostatic, Sensor Time Flow, Bioguard

### ILLUSTRATED

**A6062** (TB H6) Markwik 21 integral thermostat, bib mixer, time flow sensor, single flow horizontal outlet, 2 x ½" inlets at 200mm centres, Armitage Bioguard outlet fitted

### ILLUSTRATED PRODUCT DETAILS

#### Weights

**A6062** 5.80 KG

#### Finishes

**A6062**  Chrome (AA)

#### Materials

**A6062** Chrome Plated Brass

#### Standards

Conforms to HTM64 (2006), HTM04, HFN30

#### Special Notes

This product is fitted with an Armitage Bioguard outlet which reduces the opportunity for bio film attachment and is lined with anti-microbial copper.


Tap is activated by hand movement over the sensor and water will run for a predetermined length of time, factory pre-set at 1 minute but adjustable.

Hygienic automatic flush can be set to occur every 6, 12, 24, 48 or 72 hours.

Unique built-in thermal disinfection cleansing feature using kit S8239NU a bridging hose which is re-usable. A purging tool A4556AA is also available to facilitate initial installation or aid in system disinfection.

\* Line drawing shows recommended height over scrub up troughs. .

Flow rate regulated to maximum of 10 Litres per minute.



### ACCREDITATIONS



### FEATURES

