

Markwik 21 Panel Mixer, Demountable, Time Flow Sensor, Detachable Spout and Bioguard

ILLUSTRATED

A6245 (TB H6) Markwik 21 integral thermostat, demountable panel mixer, time flow sensor, detachable spout and Armitage Bioguard outlet fitted

ILLUSTRATED PRODUCT DETAILS

Weights

A6245 5.80 KG

Finishes

A6245  Chrome (AA)

Materials

A6245 Chrome Plated Metal

Flow rates

A6245 7.5 Litres per minute @ 3 bar pressure

Standards

Conforms to HBN 00.10, HBN 00.09 and HTM 04-01 Addendum 2013.

Special Notes

This product is fitted with an Armitage Bioguard outlet which reduces the opportunity for bio film attachment and is lined with anti-microbial copper.


Tap is activated by hand movement over the sensor and water will run for a predetermined length of time, factory pre-set at 1 minute but adjustable.

Hygienic automatic flush can be set to occur every 6, 12, 24, 48 or 72 hours.

Unique built-in thermal disinfection cleansing feature using kit S8239NU a bridging hose which is re-usable. A purging tool A4556AA is also available to facilitate initial installation or aid in system disinfection.

Flow rate regulated to maximum of 10 Litres per minute.

* Line drawing shows recommended height over scrub up troughs.



ACCREDITATIONS



1512003

FEATURES

