Silhouette 2401-3000mm Washtrough With Upstand Bespoke Sizes

ILLUSTRATED

S0661	Silhouette 2401-3000mm configurable washtrough with upstand & waste
A9209	Contour 21 Panel Mounted Soap Dispenser
A9241	Contour 21 soap bottle remote 4 feed for use with contour 21 soap dispensers
A9240	Contour 21 soap bottle remote single feed for use with contour 21 soap dispensers for all contour 21 soap dispensers
A4846	Sensorflow 21 compact tubular panel mounted 150mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, mains

OPTIONS

A4847	Sensorflow 21 compact tubular panel mounted 150mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, link

ILLUSTRATED PRODUCT DETAILS

Sizes

S0661 l:3000

Weights

S0661	53.00 KG
A9209	2.00 KG
A9241	1.00 KG
A9240	0.50 KG
A4846	1.70 KG

Materials

S0661	Solid Surface
A9209	Chrome Plated Metal
A9241	Plastic
A9240	Plastic
A4846	Chrome Plated Brass

Finishes

S0661	White (01)
A9209	Chrome (AA)
A9241	Unfinished (NU)
A9240	Unfinished (NU)
A4846	Chrome (AA)

Flow rates

A4846 3.7 Litres per minute @ 3 bar pressure

FINISH OPTIONS

(AA) Chrome

(GN) Ultra Steel

Standards

EN 695
BS EN 14296

Special Notes

1 Mains spout (A4849) and 4 link spout (A4850) to be configured as illustrated. Clean using a damp cloth or sponge. Wipe dry with a soft cloth to prevent spotting.

ACCREDITATIONS

A4847(AA)

Unified Water Label 3.70 Litres Per Minute

A4846(AA)

Unified Water Label 3.70 Litres Per Minute

WRAS APPROVED PRODUCT
121015

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Armitage Shanks